U.S. National Stage of PCT/EP03/010006

List of Current Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Claims 1 - 16 (Cancelled)

- 17. (New) An orienting mechanism for a measuring device for determining a fill level or limit level of a medium in a container, including: a pivotable, ball-shaped, clampable member, which is securable to the container and which permits a sealing of the interior of the container.
 - 18. (New) The orienting mechanism as claimed in claim 17, wherein: the sealing comprises a purely metallic seal.
 - 19. (New) The orienting mechanism as claimed in claim 17, wherein: the sealing comprises an elastomeric seal.
 - 20. (New) The orienting mechanism as claimed in claim 19, the sealing comprises an O-ring seal.
 - 21. (New) The orienting mechanism as claimed in claim 17, wherein: the measuring device comprises an ultrasonic fill level measuring device.
 - 22. (New) The orienting mechanism as claimed in claim 17, wherein: the measuring device comprises a tuning-fork limit level measuring device.
 - 23. (New) The orienting mechanism as claimed in claim 21, further including: a tube serving as a cable conduit.

U.S. National Stage of PCT/EP03/010006

- 24. (New) The orienting mechanism as claimed in claim 23, wherein: said pivotable, ball-shaped, clampable member is arranged on, or around, said tube.
- 25. (New) The orienting mechanism as claimed in claim 24, wherein: said tube is arranged displaceably in said pivotable, ball-shaped, clampable member.
- 26. (New) The orienting mechanism as claimed in claim 24, wherein: a connection apparatus is arranged on an end of said tube for a drive and/or a sensor of the fill level measuring device.
 - 27. (New) The orienting mechanism as claimed in claim 17, wherein: the measuring device is a microwave fill level measuring device.
 - 28. (New) The orienting mechanism as claimed in claim 27, further including: a tube which serves as a hollow conductor.
 - 29. (New) The orienting mechanism as claimed in claim 28, wherein: said pivotable, ball-shaped, clampable member is arranged on said tube.
- 30. (New) The orienting mechanism as claimed in claim 17, further including: a holding plate, wherein:

said pivotable, ball-shaped, clampable member is secured on a flange at or on the container by said holding plate.

31. (New) The orienting device as claimed in claim 17, wherein: said pivotable, ball-shaped, clampable member is clamped on a cover plate closing a manhole of the container.

U.S. National Stage of PCT/EP03/010006

32. (New) The orienting mechanism as claimed in claim 31, wherein: said pivotable, ball-shaped, clampable member can be swung, together with the cover plate away from the container.